

# GATORGUARD

## Firm-Grade & Flex-Grade

### The Easy, Fast & Economical Spot Repair for Alligatoring Asphalt & Divots.

*GatorGuard* is a single package, water dispersed, polymer modified, mineral filled, violet-black, cementitious asphalt coating surface treatment for alligatoring or divot scarred pavement. Polymerization via the *Carbonyte Process* and fortified with polyester fiber/select rock blends produces an easy to apply, tough and resilient coating able to withstand abuse of environment and vehicular impact while extending the service life of the pavement.



*GatorGuard* Protects the sub-base by forming a durable, water-tight covering.

#### ADVANTAGES:

- May be applied above freezing and on most damp or dry surfaces.
- High build single pass coverage.
- Tenacious adhesion. Will not delaminate.
- Rapid curing at modest temperatures.
- Contractors limited to seal coat only repairs can now participate in jobs typically requiring removal and replacement of asphalt cement.
- More cost effective repair in surfaces with minor to moderate stressed asphalt.
- Contains no bio-accumulative metals, or chemicals; contains no biocides.
- Non-hazardous in cured form; therefore, may be disposed as cured residue into any municipal landfill.

#### USES:

- Designed for application as a permanent, protective top coating of asphaltic pavement assets used as playgrounds, parking lots, industrial warehouse floors, driveways, surface streets and highways.
- An effective filler and leveler (undiluted) for shallow divots in most rigid substrates.

#### FIRM-GRADE:

HIGH TEMPERATURE, TIRE  
SCUFF RESISTANT TO POWER  
STEERING ABUSE.

#### FLEX-GRADE:

FOR STRAIGHT & ROLLING  
TRAFFIC.

